

TopPage>>Search Result>>7226

# Angular Contact Ball Bearings

Bearing No. : **NACHI 7226**

■ Bearing Type 
■ Clearance 
■ Tolerance Class

<p>Dimensions</p> <p>d = 130<sup>0</sup><sub>-0.025</sub></p> <p>D = 230<sup>0</sup><sub>-0.030</sub></p> <p>B = 40<sup>0</sup><sub>-0.250</sub></p> <p>r = 3~5 (Radial Direction)</p> <p>r = 3~8 (Axial Direction)</p> <p>r1 = 1.1~2.5 (Radial Direction)</p> <p>r1 = 1.1~4 (Axial Direction)</p> <p>a = 32</p>		<p>Dimensions</p> <p>da1(min) = 144</p> <p>da2(min) = 137</p> <p>Da1(max) = 216</p> <p>Da2(max) = 223</p> <p>ra(max) = 2.5</p> <p>ra1(max) = 1</p> <p>Mass = 6.88 kg</p>
--	--	--

<p>Basic Dynamic Load Rating Cr : <b>196,000</b> N</p> <p>Basic Static Load Rating Cor : <b>198,000</b> N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : <b>2,400</b> min<sup>-1</sup></p> <p style="padding-left: 20px;">Oil Lubrication : <b>3,100</b> min<sup>-1</sup></p>	<table border="1"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Width Variation :</td> <td><b>0.030</b></td> <td><b>0.030</b></td> </tr> <tr> <td>Radial Runout :</td> <td><b>0.030</b></td> <td><b>0.050</b></td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	<b>0.030</b>	<b>0.030</b>	Radial Runout :	<b>0.030</b>	<b>0.050</b>
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	<b>0.030</b>	<b>0.030</b>																	
Radial Runout :	<b>0.030</b>	<b>0.050</b>																	